



CHEMIX EMULSION WLL.
Bitumen emulsion provide an alternative
approach in which the bitumen is liquefied

Technical Data Sheet
Date of Issue: 02-01-2014

CHEMIX C55B5

Cationic Bitumen Emulsion

GENERAL

Chemix C55B5 is a cationic bitumen emulsion is a medium setting (CMS-1H) emulsion with medium solid content and mainly used for coated stone applications.

Chemix C55B5 is manufactured by Chemix Emulsion Co. Wll accredited to ISO 9001:2008.

SURFACING DESIGN

The design and implementation of surfacing using Chemix C55B5 should be carried out in accordance with BS 594987 and Design Manual for Roads and Bridges.

HEALTH AND SAFETY

Chemix C55B5 is not classified as hazardous to health or the environment. For further information refer to our relevant Material Safety Data Sheet.

SUPPLY

Availability, prices and conditions of sale are available within the quotation / Proforma invoice further to your enquiry.

Chemix Cationic Emulsion Properties			
Binder Content	EN 1428	53 - 57 % (m/m)	Class 5
Viscosity	EN 12846 Efflux Time (2 mm at 40 °C)	15 - 70	Class 3
Water effect on binder adhesion	EN 13614	NPD	Class 0
Breaking behavior	EN 13075-1 (Forshammar)	120 - 180	Class 5
Dangerous substances	-	NPD	-
Residual binder recovered by evaporation from cationic bituminous emulsion according to EN 13074 -1			
Consistency at intermediate service temperature	EN 1426	≤ 100	Class 3
Consistency at elevated service temperature	EN 1427	≥ 46	Class 5